

# QAA1A1

## 1-5/8" (IF70) to 1-5/8" (IF70)

Features:  
\* Low VSWR

Applications:  
\* Wireless  
\* Transmitter  
\* Laboratory Test  
\* Radar

### Electrical

Frequency:	DC~3GHz
VSWR:	1.07@DC~1000MHz max.
Dielectric Withstanding Voltage:	6000V RMS, 50Hz, at sea level, min.
Impedance of Dielectric:	5000MΩ min.
Average Power:	3.4KW@900MHz
Peak Power:	20KW max.
Impedance:	50Ω

### Mechanical

RF Connectors:	1-5/8" (IF70)
Mating Life Cycle:	100 cycles min.
ROHS Compliant:	Full ROHS compliance
Outer Conductor:	Nickel plated brass
Dielectric:	PTFE
Inner Conductor:	Silver plated brass
Waterproof:	With O-Ring

### Environmental

Temperature:	-55~+85°C
--------------	-----------


### How To Order

**QAA1A1** - 1-5/8" (IF70) to 1-5/8" (IF70), Outline A

**QAA1A1R** - 1-5/8" (IF70) to 1-5/8" (IF70) right angle, Outline B

Customization is available upon request.

### Outline Drawings



Unit: mm [in]  
Tolerance: ±0.2mm [±0.008in]