


QPD2-1000-18000-20-S

2-Way, 1~18GHz

Features:
 * Small Size
 * Low Insertion Loss

Applications:
 * Amplifiers
 * Mixers
 * Antennas
 * Laboratory Test



Electrical

Frequency:	1~18GHz
Insertion Loss ^{*1} :	1.2dB max.
Input VSWR:	1.4 max.
Output VSWR:	1.4 max.
Isolation:	18dB min.
Amplitude Balance:	±0.3dB typ.
Phase Balance:	±3° typ.
Impedance:	50Ω
Power @SUM Port:	20W max. as divider 1W max. as combiner

[1] Excluding theoretical loss 3dB.

Mechanical


Size ^{*2} :	96*32*10mm 3.78*1.26*0.394in
Connectors:	SMA Female
Mounting:	4-Φ3.2mm through-hole

[2] Exclude connectors.

Environmental

Operation Temperature:	-45~+85°C
------------------------	-----------

Outline Drawings



Unit: mm [in]
 Tolerance: ±0.5mm [±0.02in]

How To Order


QPD2-1000-18000-20-S

Customization is available upon request.


2-Way Power Divider/Combiner

Typical Performance Curves


Input VSWR vs. Frequency




Output VSWR vs. Frequency




Insertion Loss vs. Frequency



Isolation vs. Frequency



Amplitude Balance vs. Frequency



Phase Balance vs. Frequency

