QBT-0.3-110000

0.3MHz~110GHz

Features:
* Broadband
* Small Size

Applications:
* Telecom
* Satcom
* Laboratory Test
* Instrumentation

Electrical

Frequency:	0.3MHz~110GHz
Insertion Loss	4dB typ.
VSWR:	2.6 max.
Voltage:	-16~16V
Current:	400mA max.
Inductance:	220uH typ.
DC Isolation:	20dB min.
DC Impedance:	3.2Ω typ.

Mechanical

Size:	27.4*45.4*11.7mm
	1.079*1.787*0.461in
DC Connectors:	SMA Female
RF Connectors:	1.0mm
RF/DC Connectors:	1.0mm
Mounting:	4-M2mm, depth 2mm

Outline Drawings



Unit: mm [in]
Tolerance: ±0.2mm [±0.008in]

How To Order

QBT-0.3-110000-1-05- 1.0mm (f) - 1.0mm (f), DC in SMA (f)
QBT-0.3-110000-1-08- 1.0mm (f) - 1.0mm (m), DC in SMA (f)
QBT-0.3-110000-1-11- 1.0mm (m) - 1.0mm (m), DC in SMA (f)
QBT-0.3-110000-1-12- 1.0mm (m) - 1.0mm (f), DC in SMA (f)

Customization is available upon request.