

QCK-2-50-1

2.4mm Connectors, DC~50GHz, Precision type

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in the kit you can make error-corrected measurements of devices supplied with 2.4mm connectors from DC to 50 GHz.

Components

Part Number	Description	Frequency	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size		
		(GHz)	(Max.)	(°, Max.)			(mm)		
QO2C-M-50-1	2.4mm male open	DC~50	-	±2.5	Gold plated beryllium copper	Gold plated beryllium copper	-		
QO2C-F-50-1	2.4mm female open								
QS2C-M-50-1	2.4mm male short		-	±2.5					
QS2C-F-50-1	2.4mm female short								
QCT-2-C-M-50-1	2.4mm male termination		1.052	-				-	-
QCT-2-C-F-50-1	2.4mm female termination								
QW-21-CK	2.4mm torque wrench (0.9Nm torque)		-	-	Nickel plated tool steel (Head)	Alumina (Handle)	8 (Opening size)		
QA22C-MM*	2.4mm male to 2.4mm male adapter		1.12	-	-	Gold plated beryllium copper	Gold plated beryllium copper	-	
QA22C-MF*	2.4mm male to 2.4mm female adapter								
QA22C-FF*	2.4mm female to 2.4mm female adapter								
Storage Box			-	-	-	Wood		275*200*80	

*" Equal phase adapter

How To Order

- QCK-2-50-1-10** All the 10 components in one box.
- QCK-2-50-1-3M** Three in one box, including open, short and termination, male, QO2C-M-50-1, QS2C-M-50-1, QCT-2-C-M-50-1.
- QCK-2-50-1-3F** Three in one box, including open, short and termination, female, QO2C-F-50-1, QS2C-F-50-1, QCT-2-C-F-50-1.
- QCK-2-50-1-6** Six in one box, including QCK-2-50-1-3M and QCK-2-50-1-3F.

To order a single component, specify the part number in the first column.