

QLA-100-20000-20-20

0.1~20GHz, 20dB, 2.0dB

Features:
 * Broadband
 * Low Noise

Applications:
 * Wireless
 * Receiver
 * Laboratory Test
 * Radar



Electrical

Frequency:	0.1~20GHz
Gain:	20dB typ.
Gain Flatness:	±0.5dB typ.
Output Power (P1dB):	10dBm typ.
Noise Figure:	2.0dB typ.
Spurious:	-60dBc max.
Reverse Isolation:	-30dB typ.
VSWR:	1.8 typ.
Voltage:	+5V DC (Outline A) +6~12V DC (Outline B)
Current:	200mA typ.
Impedance:	50Ω

Absolute Maximum Ratings*1

RF Input Power:	+17dBm
Voltage:	+6V (Outline A) +20V (Outline B)

[1] Permanent damage may occur if any of these limits are exceeded.


Mechanical

RF Connectors: SMA Female


Environmental

Operating Temperature:	-45~+85°C
Non-operating Temperature:	-55~+125°C

Outline Drawings



Outline A



Outline B

Unit: mm [in]

Tolerance: ±0.5mm [±0.02in]

How To Order


QLA-100-20000-20-20 - Outline A

QLA-100-20000-20-20-1 - Outline B


Customization is available upon request.

Typical Performance Curves


Input VSWR vs. Frequency




Output VSWR vs. Frequency




Gain vs. Frequency



Isolation vs. Frequency



P1dB vs. Frequency



Noise Figure vs. Frequency

