

# QLA-9K-3000-43-30

9K~3000MHz, 43dB, 3dB

Features:  
 \* Broad Band  
 \* Low Noise

Applications:  
 \* Wireless  
 \* Receiver  
 \* Laboratory Test  
 \* Radar

## Electrical

Frequency:	9K~3000MHz
Gain:	43dB typ.
Gain Flatness:	±2dB max.
Gain Variation:	±1.5dB typ.
Output Power (P1dB):	15dBm min.
Noise Figure:	3dB max. (From 50MHz)
Reverse Isolation:	60dB min.
Spurious:	-60dBc max.
Input VSWR:	2 max.
Output VSWR:	2.5 max.
Voltage:	+12V DC
Current:	110~170mA

## Absolute Maximum Ratings\*1

RF Input Power:	+5dBm
Voltage:	+12.5V DC

[1] Permanent damage may occur if any of these limits are exceeded.

## Mechanical


Size*2:	38.1*21.59*9.5mm 1.5*0.85*0.375in
RF Connectors:	SMA female
Mounting:	4-Φ2.54mm through-hole

[2] Exclude connectors.

## Environmental

Operating Temperature:	-40~+75°C
Non-operating Temperature:	-55~+125°C

## Outline Drawings



Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]

## How To Order

**QLA-9K-3000-43-30**

Customization is available upon request.